

## equipment for hydraulic presses

### CID CIS CIE

Hydraulic power pack for supplying hydraulic power to presses.

Base and protection frame.

Metallic box with handles for transport.

2-stage pump for a faster return of the press cylinder (except model CIS.02 single-stage)

Quick couplings for connecting the flexible hoses.

- Model CIS.02 equipped with Heat exchanger cooling hydraulic oil for use extended in hot environments

#### OPTIONAL

- 01 - Control valve for presses mounted on power unit instead of the press
- 02 - Single phase electric motor (for model CIE.01).
- 03 - Oil reservoir with capacity 2 lt (only for model CIS.01 and CID.01)
- 04 - Increased capacity of the pump at 8/2 liters/minut

	Engine	Power kW	Max pressure bar	Max flow l/min	Tank capacity l	Dimensions l x w x h mm	Weight kg
<b>CIS.01</b>	gasoline	4,5	700	4,7 - 1,8	10	530 x 340 x 370	51
<b>CIS.02</b>	gasoline	4,5	700	3	10	520 x 400 x 400	42
<b>CID.01</b>	diesel	5	700	4,7 - 1,8	10	550 x 400 x 450	60
<b>CIE.01</b>	three phase Electric	2,2	700	4,7 - 1,8	10	530 x 340 x 370	46



**CIS.02**

### PL

Hand pump for presses.

- 2-stage pump for a faster return of the press cylinder.
- Light-alloy construction.
- Quick couplings for connecting the flexible hoses.



	Max pressure bar	Displacement		Tank capacity l	Dimensions l x w x h mm	Weight kg
		1 <sup>st</sup> stage cm <sup>3</sup>	2 <sup>nd</sup> stage cm <sup>3</sup>			
<b>PL.262</b>	700	13	3	2,5	565 x 125 x 170	8

### TF

Kit of flexible hoses with quick couplings.

Lengths: 3, 6, 10, 15, 20, 30, 40, 50, 60 m (specify the length needed).



### GR

Quick couplings for connecting two flexible hoses.

