

# 21.12



Anti-twisting galvanized steel rope specifically designed for stringing operations. Made up of 12 braided strands. High resistant to break, antitwisting, flexible, safe and easy to handle. The linear contact between the braided strands grants a low stress on the rope. Supplied wound up on steel or wooden reels.

	Nominal diameter	Breaking load	Weight	Standard Lengths (*)
	mm	kN	kg	m
21.12.08	8	44	0,22	1000
21.12.10	10	72	0,35	1000
21.12.13	13	105	0,55	1000
21.12.16	16	163	0,80	1000
21.12.18	18	235	1,07	1000
21.12.20	20	268	1,24	1000
21.12.22	22	330	1,56	900
21.12.24	24	380	1,80	800
21.12.28	28	480	2,80	600

(\*) other lengths on request

### HIGH RESISTANCE (18 strands)

	Nominal diameter	Breaking load	Weight	Standard Lengths (*)
	mm	kN	kg	m
21.18.22	22	402	1,86	900
21.18.24	24	490	2,34	800
21.18.30	30	720	3,25	500

### OPTIONAL DEVICES

- 146.2 Spliced eyes at both ends
- 146.3 Clamped eyes at both ends

Dimensions and weights are without optional devices. All data may change without notice. Images and drawings are indicative only.