

**TRAILER FOR TRANSPORT CABLE DRUM
With manual lifting of reel**

1. General Parameters:

model: F10.25.1		model: F10.35.1	
Total weight:	2700 kg,	Total weight:	3500 kg
load capacity:	2000 kg	load capacity:	2500 kg
Width of the frame:	1.800 mm	Width of the frame:	1.900 mm
Drum width max:	1200 mm	Drum width max:	1650 mm
max drum diameter:	2.200 mm	max drum diameter:	2.700 mm
max Speed:	80 km/h	max Speed:	80 km/h

* In the motorised options, the load capacity of the trailer is reduced

2. Standard :

- Steel structure hot-dip galvanized steel
- Suspension: two centrally axles suspended
- Axles: braked AL-KO Germany
- Wheels: 4 x 185 R 14C, 4 x 195 R 14C
- Brake: AL-KO overrun device,
- Hook: ball type
- Height of hook for ball hook to the Ground - 450-500 mm
- AL-KO manual drum winch in safety guard,
- Two rear parking supports,
- Drawbar bracket with smooth (stepless) adjustable height
- Complete 12 or 24V electrical installation,
- Tandem galvanized mudguards,
- Complete set of documents necessary to register the vehicle



3. Optional:

- Drum drive - winding and pulling the cable – motorised with engine,
- Drawbar with adjustable height in the range 400 to 1000 mm,
- Coupling for truck – „eye” 40 mm

