

S LUB 100

TECHNICAL INFORMATION

S LUB 100 is a special lubricant for fiber optical installation for min and micro cable for blowing machine cable installer. It's a water emulsion of different kind of polymers.

S LUB 100 is a water base product with high lubricant efficiently. It's reduce dramatically the friction. S LUB is white liquid little bit viscosity.

S LUB 100 adhere perfectly at the cable surface or at the internal surface of the pipe. It's leave a very tiny film of lubricant and does not make the glue effect. Product Use: Cable and Duct Prelubrication

S LUB 100 has the same base products of S LUB 10 but is much more performance due a specific additives very active in this field to reduce the friction.

Suggested Uses quantities for 1.000 mt

Uses:

Shake the bottle before use, then put the product inside in the duct. Then pre-lubricant the pipe with a little piece of sponge pushed by air compress.

The product is also suitable for blowing machine with oil dispenser to lubricating the fiber during the pushing.

The S LUB 100, also can be useful to lubricate the fiber optic before or after blowing machine. It's depend on the appliance with iron wheel or with rubber wheel.

internal duct diam Ø mm	Quantities of product	How much the duct must be fill of the product (different kind of measure for the same quantities)
4 mm	5 ml	≈ 30 cm
8 mm	10 ml	≈ 20 cm
12 mm	15 ml	≈ 15 cm

Aspect	White liquid tiny viscosity
Odour	characteristic
Viscosity	30 sec. Ford cup diam. mm 4 at 20C°
Spefigic gravity	1,030 +- 0,03 gr/cm ³
pH	7,5 +- 0,5
Inflammability	non infiammabile
Temperature	0° + 70° C.