

C-780 Overhead Line Construction Winch - 3 Tonne Capacity

Designed to give reliable, flexible winching system to meet all 11/33kV work, together with some 66kV and 132kV maintenance requirements, the system employs a range of drums to suit particular applications.

The powerful winch is mounted on a robust steel chassis with a single axle trailer facility for site manoeuvrability. The engine fitted with electric start, powers the drive spindle of the drum via a gearbox and hydraulic circuit, which is designed to achieve smooth, variable control of the winding operation in either direction. The powered hydraulic drum lifting device, together with hydraulic stabilising jacks provides safe drum handling. Hydraulic layering device fitted as standard.



Specification

Capacity:	3 tonne at 250mm dia
Engine:	Diesel or Petrol
Rope Speed:	0-100 metres/min adjustable)
Rope Drums:	See options
Drum Dia:	1100mm Maximum
Drum Width:	1075mm Maximum (If using a solid wooden drum)
Length:	3100mm
Width:	2300mm
Height:	1400mm (without drums)
Weight:	1100kg (net)

****Note: Winch supplied fitted with towing socket for use with 50mm ball as standard. Other systems available on request.**

Product No

Description

C-780-30	Overhead Line Construction Winch 3 Ton Petrol Engine
C-780-30-01	Overhead Line Construction Winch 3 Ton Diesel Engine
C-780-30-01-C	Overhead Line Construction Winch 3 Ton Diesel Engine c/w Oil Cooler

OPTIONAL EXTRAS

Product No

Description

C-780-05	Triple Drum 8mm Dia x 1500 metres Paralane Rope – 3 off required
C-1002-10-F	Weatherproof Cover
C-780-21	Torque Arm Assy c/w Locking Collar for use with wooden drums

CONDUCTOR REFURBISHING

Product No

Description

C-780-07	Triple split steel drum for old conductors. Drums are split to ease removal of old conductors – 3 off required
C-780-06-02	Single split steel drum for old conductors. Drum is split to ease removal of old conductors.