




LED TECHNOLOGY

2600 sqm
Illuminated area

Patented mast
emergency system



PLUG-IN Line



AMIN POWER ENERGY

+48 603 442 277

+48 691 442 270

Zielone Wzgórze 6, 67-210 Głogów

biuro@powerenergy.com.pl



X-CHAIN
4x160W LED - 7M

T-ZERO PRO

X-CHAIN 4x160W LED - 7M T-ZERO^{PRO}




FEATURES

- Multi-directionally adjustable and tiltable floodlights
- 5 sections vertical tower 7meters, 340° rotatable
- **Manual lifting system by winch complete with auto-braking system**
- Galvanized metalworks
- 80 µm powder coating
- **Very compact dimensions for easy handling & transportability, up to 33 units per truck**
- Light weight for improved manoeuvrability
- Central lifting eye forklift pockets for effective handling
- Guided main coiled cable to avoid damage during tower operation
- Circuit breaker for electrical protection against overload
- Certified wind stability up to 110 km/h
- 4 extendable & height adjustable stabilizers
- On board levels for guidance during stabilization
- **Patented mast emergency brake which prevents the falling of the mast in case of cable failure**
- Winch cover
- Top electrical box protection cover
- 2 Retractable galvanized handles
- **Light Sensor as standard feature**
- Bolted Central lifting eye



The first lighting tower in the market that has a patented mast emergency brake system to improve safety of the operators on site
Registration number: 102017000044431



Dimensions & weight	Dimensions min (mm)		Dimensions max(mm)		Total weight (kg)
	1200x850x2100 (LxWxH)		1850x1450x7000 (LxWxH)		300
Floodlights	Type	Power (each)	Floodlights number	IP level	Illuminated area (sqm)
	Led	160W	4	65	2600
Mast	Lifting method	Max Height	Max Wind Speed	Rotation	Patented mast emergency system
	Manual	7 m	110 km/h	340°	yes
Input&output	Inlet plug	Outlet socket	General	Tower lifting metod	Trailer type
	32A - 230V	32A - 230V		Manual	Hand trolley



AMIN POWER ENERGY
+48 603 442 277
+48 691 442 270
Zielone Wzgórze 6, 67-210 Głogów
biuro@powerenergy.com.pl

