



Operation: **ENGINE POWERED** fuel tank capacity 80 litres **Kubota Z482** 



## **AMIN POWER ENERGY**

+48 603 442 277 +48 691 442 270 Zielone Wzgórze 6, 67-210 Głogów biuro@powerenergy.com.pl

















## **FEATURES**

- Multi-directionally adjustable and tiltable floodlights
- 7 sections vertical tower 8 m, 340° rotatable
- Galvanized metalworks
- 80 µm powder coating
- Central lifting eye, forklift pockets for effective handling
- Plug & play, colour coded cables and connectors
- Guided main coiled cable to avoid damage during tower operation
- Control panel alarms for engine proteciton and fuel level indicator
- Circuit breaker for electrical protection against overload
- External emergency stop button
- Certified wind stability up tp 80 km/h
- 5 height adjustable stabilizers
- On board levels for guidance during stabilization











Dimensions & weight	Dimensions min (mm)				Dimensions max(mm)				Total w	Total weight (kg)		
	1830x1370x2560 (LxWxH)				2320x2570x8000 (LxWxH)				706	706		
Floodlights	Туре		Power (each)		Floodlights numb		•	Illuminated area (sqm)				
	LED		320W		4			5000	5000			
Mast	Lifting method		Max Height		Max Wind Speed		F	Rotation		Options		
	Manual		8 m		80 km/h		3	340°		Homologated road trailer		
Alternator	Model	Fre	Frequency (Hz)		Insulation class		Degree of prot		Single phase voltage		Auxiliary outlets	
	Synchronous	50	50		Н		IP 23		3,5kVA - 230V		1 kVA	
Engine	Model	Fuel	r.p.m.		Tank capacity (I)		Consumption (I/		h) Ru	nning time	Noise level dB(A) at 7m	
	Kubota Z482*	Diesel	el 1500		80		0,55		145 h		65	

<sup>\*</sup> May vary based on stock availability. However, Yanmar primary equivalent brand eventually will be used





## AMIN POWER ENERGY

+48 603 442 277 +48 691 442 270 Zielone Wzgórze 6, 67-210 Głogów biuro@powerenergy.com.pl