

Gas,oil &mining operations

Special events

Military applications 4200 Sqm
Illuminated area

ENGINE POWERED Line



Operation: **ENGINE POWERED** fuel tank capacity 80 litres **Kubota Z482**



AMIN POWER ENERGY

10011

X-START

TRIME

+48 603 442 277 +48 691 442 270 Zielone Wzgórze 6, 67-210 Głogów biuro@powerenergy.com.pl





6x160W - LED - 8M













FEATURES

- Multi-directionally adjustable and tiltable floodlights
- 7 sections vertical tower 8 m, 340° rotatable
- Galvanized metalworks
- 80 µm powder coating
- Central lifting eye, forklift pockets for effective handling
- Plug & play, colour coded cables and connectors
- Guided main coiled cable to avoid damage during tower operation
- Control panel alarms for engine proteciton and fuel level indicator
- Circuit breaker for electrical protection against overload
- External emergency stop button
- Certified wind stability up tp 80 km/h
- 5 height adjustable stabilizers
- On board levels for guidance during stabilization











Dimensions & weight	Dimensions min (mm)				Dimensions max(mm)				Tota	Total weight (kg)		
	1830x1370x256	0 (LxWx	(WxH)		2320x2570x8000 (LxWxH)				695	695		
Floodlights	Туре	Po	Power (each)		Floodlights number			Illuminated are		a (sqm)		
	LED	16	160W		6			4200				
Mast	Lifting method		Max Height		Max Wind Sp	eed	Rotation			Options		
	Manual 8 m		8 m		80 km/h		340°			Homologated road trailer		
Alternator	Model	Fred	Frequency (Hz)		Insulation class		of p	protection Single phase volta		e phase voltage	Auxiliary outlets	
	Synchronous	50	50		Н		IP 23		3,5kVA - 230V		1 kVA	
Engine	Model	Fuel	r.p.m.		Tank capacity (I) C	Consumption (I/		/h)	Running time	Noise level dB(A) at 7m	
	Kubota Z482*	Diesel	sel 1500		80	0	0,55			145 h	65	

^{*} May vary based on stock availability. However, Yanmar primary equivalent brand eventually will be used





AMIN POWER ENERGY

+48 603 442 277 +48 691 442 270 Zielone Wzgórze 6, 67-210 Głogów biuro@powerenergy.com.pl