



AMIN POWER ENERGY

+48 603 442 277 +48 691 442 270 Zielone Wzgórze 6, 67-210 Głogów biuro@powerenergy.com.pl





S LUB 10 TECHNICAL INFORMATION – rev 6.3

S LUB is a special lubricant for fiber optical installation for min and micro cable with blowing machine. It's a water emulsion of different kind of polymers.

S LUB is a water base product with high efficiently of lubricant. It's reduce dramatically the friction. S LUB is white liquid little bet viscosity.

S LUB adhere perfectly at the cable surface or at the internal surface of the pipe. It's leave a very tiny film of lubricant and does not make the glue effect. Product Use: Cable and Duct Prelubrication

Suggest Uses quantities for 1.000 mt

| diam Ø mm internal pipe | Quantities of product | How much the pipe must be feel of the product (different kind of measure for the same quantities) |
|----------------------------|-----------------------|---|
| 4 mm | 8 ml | 55-60 cm |
| 8 mm | 15 ml | 30-35 cm |
| 12 mm | 22 ml | 20-22 cm |

The real quantities can be change due to a condition of the pipe or how is difficult the pipe long.

Use:

Shake the bottle before use, then put the product inside in the pipe. Then pre-lubricant the pipe with a little piece of sponge.

The product is also suitable for blowing machine with oil dispenser to lubricating the fiber during the pushing.

The S LUB 10, also can be useful to lubricate the fiber optic before or after blowing machine. It's depend on the appliance with iron wheel or with rubber wheel.





AMIN POWER ENERGY

+48 603 442 277 +48 691 442 270 Zielone Wzgórze 6, 67-210 Głogów biuro@powerenergy.com.pl





Technical Specification:

White liquid tiny viscosity Aspect

Odour none

Viscosity 15 sec. Ford cup diam. mm 4 at 20C°

Spefigic gravity 1,030 + 0.03 gr/cm

7,5 + 0,5рΗ

Inflammability non infiammabile Temperature $-10^{\circ} + 65^{\circ} \text{ C}.$

Biodegradability Biodegradability in 90% The product is not toxic. Toxic