




F162

Welded and painted steel reel.

OPTIONAL DEVICES

- 02 Pair of standard dials.
- 03 Pair of dials equipped with ball bearings.
- 04 Reinforced reel, made of square tubular (30% heavier than the standard version).




| | Dimensions mm | | | | | | Weight (without rope) kg |
|-----------------|------------------|------|------|------|-----|-----|--------------------------------|
| | A | B | C | D | E | F | |
| F162.075 | 750 | 530 | 460 | 245 | | 50 | 38 |
| F162.110 | 1100 | 560 | 460 | 570 | 420 | 50 | 66 |
| F162.140 | 1400 | 560 | 460 | 570 | 420 | 50 | 105 |
| F162.160 | 1600 | 560 | 460 | 570 | 420 | 50 | 120 |
| F162.190 | 1900 | 560 | 460 | 570 | 420 | 50 | 140 |
| F162.220 | 2200 | 1560 | 1400 | 1010 | 420 | 100 | 950 |

F164

Welded and painted steel conical reel with openable side.

OPTIONAL DEVICES

- 02 Pair of standard dials.
- 03 Pair of dials equipped with ball bearings.
- 05 Drum core covered with steel sheet.



| | Dimensions mm | | | | | | Weight (without rope) kg |
|-----------------|------------------|------|------|------|-----|-----|--------------------------------|
| | A | B | C | D | E | F | |
| F164.075 | 750 | 530 | 460 | 245 | | 50 | 50 |
| F164.110 | 1100 | 560 | 460 | 570 | 420 | 50 | 85 |
| F164.140 | 1400 | 560 | 460 | 570 | 420 | 50 | 115 |
| F164.160 | 1600 | 560 | 460 | 570 | 420 | 50 | 130 |
| F164.190 | 1900 | 560 | 460 | 570 | 420 | 50 | 220 |
| F164.220 | 2200 | 1310 | 1170 | 1010 | 420 | 100 | 1050 |

| Rope diameter (mm) | REEL CAPACITY (meters of rope) | | | | | |
|--------------------|--------------------------------|----------------------|----------------------|----------------------|----------------------|----------------------|
| | F162.060 F164.060 | F162.110 F164.110 | F162.140 F164.140 | F162.160 F164.160 | F162.190 F164.190 | F162.220 F164.220 |
| 6 | 2000 | 6300 | 13000 | 17000 | 25000 | - |
| 7 | 1500 | 4500 | 9000 | 12000 | 18000 | - |
| 8 | 1200 | 3500 | 6000 | 5500 | 14000 | - |
| 9 | 900 | 2800 | 5400 | 7500 | 11000 | - |
| 10 | 800 | 2300 | 4400 | 6000 | 9000 | 33000 |
| 11 | 500 | 1900 | 3600 | 5000 | 7500 | 31000 |
| 12 | 450 | 1600 | 3000 | 4200 | 6000 | 22000 |
| 13 | 400 | 1400 | 2600 | 3600 | 5400 | 19000 |
| 14 | 300 | 1250 | 2200 | 3000 | 4600 | 16000 |
| 16 | 250 | 1000 | 1700 | 2400 | 3500 | 13000 |
| 18 | - | 800 | 1300 | 1900 | 2800 | 10000 |
| 20 | - | 650 | 1100 | 1600 | 2200 | 8000 |
| 22 | - | 500 | 900 | 1200 | 1900 | 6000 |
| 24 | - | - | 750 | 1000 | 1500 | 5000 |
| 26 | - | - | 650 | 900 | 1300 | 4500 |
| 28 | - | - | 560 | 800 | 1100 | 4000 |
| 30 | - | - | 490 | 700 | 1000 | 3500 |
| 32 | - | - | 430 | 600 | 850 | 3000 |

Performances of the machine without optional devices, at sea level and temperature 20°C.
Dimensions and weights are without optional devices. All data may change without notice. Images and drawings are indicative only.