




LED TECHNOLOGY

4200 sqm
Illuminated area

ENGINE POWERED Line



Operation: **ENGINE POWERED**
fuel tank capacity 220 litres
Kubota Z482


X-BOX 6X160W 48V LED - 8,5M



FEATURES

- Multi-directionally adjustable and tiltable floodlights
- 7 sections hydraulic vertical tower 8,5 m, 340° rotatable
- **Standard light sensor for machine power on and off**
- Galvanized metalworks
- 80 µm powder coating
- **Very compact dimensions, up to 22 units per truck**
- Central lifting eye longitudinal and transversal forklift pockets for effective handling
- Plug & play, colour coded cables and connectors
- Guided main coiled cable to avoid damage during tower operation
- Digital control panel and fuel level indicator
- Circuit breaker for electrical protection against overload
- External emergency stop button
- **Fully banded tank, 110%**
- Certified wind stability up to 110 km/h
- 4 extendable & height adjustable stabilizers
- On board levels for guidance during stabilization

LOW 
reduced
transport costs

RUNNING TIME
 220 litres tank
400 h
Low fuel consumption

NOISE 
level 65 dB(A) at 7m

4200 sqm
illuminated area 


VERY COMPACT dimensions

units
22 per truck


Dimensions & weight	Dimensions min (mm)		Dimensions max(mm)		Total weight (kg)		
		1200x1200x2560 (LxWxH)		2390x2390x8500 (LxWxH)		1013	
Floodlights	Type	Power (each)	Floodlights number	Options	Illuminated area (sqm)		
	Led	160W	6	Timer	4200		
Mast	Lifting method	Max Height	Max Wind Speed	Rotation			
	Hydraulic	8,5 m	110 km/h	340°			
Alternator	Model	Frequency (Hz)	Insulation class	Degree of protection	Single phase voltage	Auxiliary outlets	
	Synchronous	50	H	IP 23	3,5kVA - 230V	1,2 kVA	
Engine	Model	Fuel	r.p.m.	Tank capacity (l)	Consumption (l/h)	Running time	Noise level dB(A) at 7m
	Kubota Z482*	Diesel	1500	220	0,55	400 h	65

* May vary based on stock availability. However, Yanmar primary equivalent brand eventually will be used

 **TRIME**® Sales Dept. +39 0382 406 252
www.trime.it - info@trime.it
Lighting Towers