



UP200 MAX PULL 200 KN

Hydraulic puller 200 kN. Fit to pull one rope in laying underground transmission cables and pipes refurbishing.



- MAX PULL
200 kN
- MAX SPEED
21 m/min
- MAX ROPE
22 mm
- CAPSTANS
2 x Ø 380 mm

FEATURES

CAPSTANS	2 x Ø 380 mm
MAX ROPE DIAMETER	22 mm
DIMENSIONS L x W x H	4890 x 2170 x 1990 mm
WEIGHT (WITHOUT ROPE)	4300 kg

REEL

CAPACITY OF STEEL ROPE:	
Ø 18 mm	1500 m
Ø 22 mm	1000 m

CONFIGURATION

- Multi-grooved steel capstans
- Control panel equipped with built-in electronic instrument DEG 4.0 - 7" large graphic colour display and a USB port
- Metallic cover
- Electronic instrument by-pass
- Device for pipe refurbishing. Fit for setting the max. pull force which allows to maintain the force set even at speed 0 m/min.
- Maintenance-free load cell reading system
- Safety negative hydraulic brake
- Oil cooling system
- Rope guiding pulley
- Built-in reel-winder with automatic rope-winder
- Chassis with tandem rigid axle, adjustable towing bar and manual parking brake fit for towing at low speed on the job site
- Four adjustable mechanical stabilisers
- Anchoring and lifting points

PULL PERFORMANCES

MAX PULL	200 kN
SPEED AT MAX PULL	8 m/min / 8 m/min *
MAX SPEED	21 m/min / 30 m/min *
PULL AT MAX SPEED	55 kN

ENGINE

FEEDING	Diesel
POWER	55 kW / 55 kW *
COOLING	water
STARTING	12 V

OPTIONAL DEVICES

- 005.1CE Chassis with tandem damped axle, towing bar adjustable in height, pneumatic braking system, ABS system and lights fit for towing the machine on road at max. speed 80 km/h. EC-Type approved set. Homologation - Registration Excluded
- 037.2 Compact remote control by cable. Cable length = 10 m
- 038.1 Radio remote control. Complete with display and 5 m long back-up cable.
- 069.5 Printer with accessories
- 051.3 Motorised rubber crawler system. Complete with front hydraulic plough and radio-remote control for the crawler system and the machine pulling operations.
- 107 OLS - OMAC Link System. GPS geolocation + remote monitoring and diagnostics.

* According to the EC directive 97/68/CE with subsequent amendments and additions.

Performances of the machine without optional devices, at sea level and temperature 20°C.
Dimensions and weights are without optional devices. All data may change without notice. Images and drawings are indicative only.