




## C110.A

Galvanised steel cable and rope entrance device.



|                  | bending radius | Ø socket | weight |
|------------------|----------------|----------|--------|
|                  | mm             | mm       | kg     |
| <b>C110.A.07</b> | 420            | 75       | 16,5   |
| <b>C110.A.09</b> | 420            | 90       | 17,0   |
| <b>C110.A.10</b> | 420            | 101      | 17,5   |
| <b>C110.A.12</b> | 420            | 114      | 18,0   |
| <b>C110.A.15</b> | 420            | 152      | 18,5   |
| <b>C110.A.17</b> | 420            | 168      | 19,0   |

## C110.B

Galvanised steel cable and rope entrance device.



|                  | bending radius | Ø socket | weight |
|------------------|----------------|----------|--------|
|                  | mm             | mm       | kg     |
| <b>C110.B.07</b> | 1000           | 75       | 22,0   |
| <b>C110.B.09</b> | 1000           | 90       | 22,5   |
| <b>C110.B.10</b> | 1000           | 101      | 23,0   |
| <b>C110.B.12</b> | 1000           | 114      | 23,7   |
| <b>C110.B.15</b> | 1000           | 152      | 24,5   |
| <b>C110.B.17</b> | 1000           | 168      | 25,0   |

## C110.C

Galvanised spare socket for rope entrance devices C110.A and C110.B.



|                  | Ø external | weight |                  | Ø external | weight |
|------------------|------------|--------|------------------|------------|--------|
|                  | mm         | kg     |                  | mm         | kg     |
| <b>C110.C.07</b> | 75         | 1,0    | <b>C110.C.12</b> | 114        | 1,9    |
| <b>C110.C.09</b> | 90         | 1,5    | <b>C110.C.15</b> | 152        | 2,0    |
| <b>C110.C.10</b> | 101        | 1,7    | <b>C110.C.17</b> | 168        | 2,1    |

## C110.M


Galvanised cable protector with roller.



|                  | Ø external | weight |                  | Ø external | weight |
|------------------|------------|--------|------------------|------------|--------|
|                  | mm         | kg     |                  | mm         | kg     |
| <b>C110.M.05</b> | 51         | 4,0    | <b>C110.M.10</b> | 114        | 6,0    |
| <b>C110.M.06</b> | 61         | 4,2    | <b>C110.M.12</b> | 133        | 7,0    |
| <b>C110.M.07</b> | 75         | 4,5    | <b>C110.M.13</b> | 140        | 7,3    |
| <b>C110.M.09</b> | 89         | 5,0    | <b>C110.M.15</b> | 152        | 7,5    |

## C110.P

Galvanised cable entrance device with adjustable double protection.



|                  | Ø external | weight |                  | Ø external | weight |
|------------------|------------|--------|------------------|------------|--------|
|                  | mm         | kg     |                  | mm         | kg     |
| <b>C110.P.05</b> | 51         | 2,5    | <b>C110.P.13</b> | 140        | 6,4    |
| <b>C110.P.07</b> | 76         | 3,5    | <b>C110.P.15</b> | 152        | 6,6    |
| <b>C110.P.09</b> | 89         | 4,2    | <b>C110.P.17</b> | 168        | 7,4    |
| <b>C110.P.10</b> | 114        | 5,0    | <b>C110.P.20</b> | 194        | 8,3    |
| <b>C110.P.12</b> | 133        | 6,2    |                  |            |        |