



ENGINE POWERED Line





max height 8,5 m



FEATURES

- Multi-directionally adjustable and tiltable floodlights
- 7 sections hydraulic vertical tower 8,5 m, 340° rotatable
- Standard light sensor for machine power on and off
- Galvanized metalworks
- 80 µm powder coating
- Very compact dimensions, up to 22 units per truck
- Central lifting eye longitudinal and transversal forklift pockets for effective handling
- Plug & play, colour coded cables and connectors
- Guided main coiled cable to avoid damage during tower operation
- Digital control panel and fuel level indicator
- Circuit breaker for electrical protection against overload
- External emergency stop button
- Fully bunded tank, 110%
- Certified wind stability up tp 110 km/h
- 4 extendable & height adjustable stabilizers
- On board levels for guidance during stabilization







Dimensions & weight	Dimensions min (mm)				Dimensions max(mm)					Total weight (kg)			
	1200x1200x2560 (LxWxH)				2390x2390x8500 (LxWxH)				10	1030			
Floodlights	Туре		Power (each)		Floodlights number			Options		Illuminated area (sqm)		area (sqm)	
	Led		320W		4			Timer		9300			
Mast	Lifting method		Max Height		Max Wind Speed			Rotation		Options			
	Hydraulic		8,5 m		110 km/h		340°			Timer			
Alternator	Model		Frequency (Hz)		Insulation class		Degree of protection		Single phase volt		se voltage	Auxiliary outlets	
	Synchronous		50		Н		IP 23		3,5kVA - 2		30V	1 kVA	
Engine	Model	Fuel	r.p.m.		Tank capacity (I)		Consumption (I/I		'h) Runn		iing time	Noise level dB(A) at 7m	
	Kubota Z482*	Diese	el 1500		220		0,55			400 I	1	65	

* May vary based on stock availability. However, Yanmar primary equivalent brand eventually will be used



reduced transport costs

(a)