



TRIME®

Lighting Towers



LED TECHNOLOGY

9300 sqm


Illuminated area



Construction
& work sites



Gas, oil & mining
operations



Special
events




Emergency



Military
applications

ENGINE POWERED Line



Operation: **ENGINE POWERED**
fuel tank capacity 125 litres
Kubota Z482

X-NOVA

4x320W - LED - 8M

X-NOVA

4x320W - LED - 8M



FEATURES

- Multi-directionally adjustable and tiltable floodlights
- 7 sections vertical tower 8 m, 340° rotatable
- Galvanized metalworks
- 80 µm powder coating
- Central lifting eye, forklift pockets for effective handling
- Plug & play, colour coded cables and connectors
- Guided main coiled cable to avoid damage during tower operation
- Control panel alarms for engine protection and fuel level indicator
- Circuit breaker for electrical protection against overload
- External emergency stop button
- Certified wind stability up to 80 km/h
- 5 height adjustable stabilizers
- On board levels for guidance during stabilization

Cost Effective

RUNNING TIME
125 litres tank
215 h
Low fuel consumption

NOISE
level 65 dB(A) at 7m

9300 sqm
illuminated area

18
units
per container 40" HQ

Dimensions & weight	Dimensions min (mm)			Dimensions max(mm)		Total weight (kg)	
	1825x1245x2504 (LxWxH)			2445x1245x8000 (LxWxH)		706	
Floodlights	Type	Power (each)		Floodlights number		Illuminated area (sqm)	
	LED	320W		4		9300	
Mast	Lifting method	Max Height		Max Wind Speed		Rotation	Options
	Manual	8 m		80 km/h		340°	Homologated road trailer
Alternator	Model	Frequency (Hz)		Insulation class	Degree of protection	Single phase voltage	Auxiliary outlets
	Synchronous	50		H	IP 23	3,5kVA - 230V	1 kVA
Engine	Model	Fuel	r.p.m.	Tank capacity (l)	Consumption (l/h)	Running time	Noise level dB(A) at 7m
	Kubota Z482*	Diesel	1500	125	0,55	215 h	65

* May vary based on stock availability. However, Yanmar primary equivalent brand eventually will be used