

UP100.B MAX PULL 100 kN

Hydraulic puller 100 kN. Fit to pull one rope in laying underground transmission cables and pipes refurbishing.



	MAX PULL 100 kN
	MAX SPEED 50 m/min
	MAX ROPE 16 mm
	CAPSTANS 2 x Ø 300 mm

FEATURES

CAPSTANS	2 x Ø 300 mm
MAX ROPE DIAMETER	16 mm
DIMENSIONS L x W x H	4385 x 1760 x 1615 mm
WEIGHT (WITHOUT ROPE)	2300 kg

REEL

CAPACITY OF STEEL ROPE:	
Ø 16 mm	850 m
Ø 14 mm	1100 m
Ø 12 mm	1500 m

CONFIGURATION

- Multi-grooved steel capstans
- Control panel equipped with built-in electronic instrument DEG 4.0 - 7" large graphic colour display and a USB port
- Metallic cover
- Electronic instrument by-pass
- Maintenance-free load cell reading system
- Safety negative hydraulic brake
- Oil cooling system
- Rope guiding pulley
- Built-in reel-winder with automatic rope-winder
- Chassis with tandem damped axle, adjustable towing bar, overrun braking system and lights fit for towing on roads (homologation-registration excluded)
- Four adjustable mechanical stabilisers
- Anchoring and lifting points

PULL PERFORMANCES

MAX PULL	100 kN
SPEED AT MAX PULL	12,5 m/min
MAX SPEED	50 m/min
PULL AT MAX SPEED	25 kN

ENGINE

FEEDING	Diesel
POWER	42 kW
COOLING	water
STARTING	12 V

OPTIONAL DEVICES

- 037.2** Compact remote control by cable. Cable length = 10 m
- 038.1** Radio remote control. Complete with display and 5 m long back-up cable.
- 069.5** Printer with accessories
- 082** Device for pipe refurbishing. Fit for setting the max. pull force which allows to maintain the force set even at speed 0 m/min.
- 051.3** Motorised rubber crawler system. Complete with front hydraulic plough and radio-remote control for the crawler system and the machine pulling operations.
- 107** OLS - OMAC Link System. GPS geolocation + remote monitoring and diagnostics.

* According to the EC directive 97/68/CE with subsequent amendments and additions.