


# UP200 MAX PULL 200 KN

Hydraulic puller 200 kN. Fit to pull one rope in laying underground transmission cables and pipes refurbishing.

	<b>MAX PULL</b> 200 kN
	<b>MAX SPEED</b> 30 m/min
	<b>MAX ROPE</b> 22 mm
	<b>BULL-WHEELS</b> 2 x Ø 380 mm



## FEATURES

<b>BULL-WHEELS</b>	2 x Ø 380 mm
<b>NUMBER OF GROOVES</b>	11
<b>MAX ROPE DIAMETER</b>	22 mm
<b>DIMENSIONS L x W x H</b>	5400 x 2350 x 2400 mm
<b>WEIGHT (WITHOUT ROPE)</b>	6200 kg

## PULL PERFORMANCES

<b>MAX PULL</b>	200 kN
<b>SPEED AT MAX PULL</b>	8 m/min / 8 m/min *
<b>MAX SPEED</b>	30 m/min
<b>PULL AT MAX SPEED</b>	55 kN

## REEL

<b>CAPACITY OF STEEL ROPE:</b>	
<b>Ø 18 mm</b>	2500 m
<b>Ø 22 mm</b>	2100 m

## ENGINE

<b>FEEDING</b>	Diesel
<b>POWER</b>	55 kW / 55 kW *
<b>COOLING</b>	water
<b>STARTING</b>	12 V

## CONFIGURATION

- Multi-grooved steel bull-wheels
- Control panel equipped with built-in electronic instrument DEG 4.0 - 7" large graphic colour display and a USB port
- Metallic cover
- Electronic instrument by-pass
- Device for pipe refurbishing. Fit for setting the max. pull force which allows to maintain the force set even at speed 0 m/min
- Maintenance-free load cell reading system
- Safety negative hydraulic brake
- Oil cooling system
- Rope guiding pulley
- Built-in reel-winder with automatic rope-winder
- Chassis with tandem rigid axle, adjustable towing bar and manual parking brake fit for towing at low speed on the job site
- Four adjustable mechanical stabilisers
- Anchoring and lifting points

## OPTIONAL DEVICES

- 005.1CE** Chassis with tandem damped axle, towing bar adjustable in height, pneumatic braking system, ABS system and lights fit for towing the machine on road at max. speed 80 km/h. EC-Type approved set. Homologation - Registration Excluded
- 037.2** Compact remote control by cable. Cable length = 10 m
- 038.1** Radio remote control. Complete with display and 5 m long back-up cable
- 069.5** Printer with accessories
- 051.3** Motorised rubber crawler system. Complete with front hydraulic plough and radio-remote control for the crawler system and the machine pulling operations
- 107** OLS - OMAC Link System. GPS geolocation + remote monitoring and diagnostics

\* According to the EC directive 97/68/CE with subsequent amendments and additions.

Performances of the machine without optional devices, at sea level and temperature 20°C.

Dimensions and weights are without optional devices. All data may change without notice. Images and drawings are indicative only.