





# P30.U.B MAX PULL 30 KN

Hydraulic puller fit to pull one rope in laying underground transmission cables and fibre-optic cables.

	<b>MAX PULL</b> 30 kN
	<b>MAX SPEED</b> 3 m/min
	<b>MAX ROPE</b> 13 mm
	<b>BULL-WHEELS</b> 2 x Ø 300 mm



## FEATURES

<b>BULL-WHEELS</b>	2 x Ø 300 mm
<b>NUMBER OF GROOVES</b>	6
<b>MAX ROPE DIAM.</b>	13 mm
<b>DIMENSIONS</b>	2,30x1,45x1,55 m
<b>WEIGHT</b>	950 kg

## PULL PERFORMANCES

<b>MAX PULL</b>	30 kN
<b>SPEED AT MAX PULL</b>	15 m/min
<b>MAX SPEED</b>	50 m/min
<b>SPEED AT 20 kN</b>	21,7 m/min

## ENGINE

<b>FEEDING</b>	diesel
<b>POWER</b>	25 hp / 18,6 kW*
<b>COOLING</b>	liquid
<b>ELECTRIC PLANT</b>	12 V

## CONFIGURATION

- 1 hydraulic circuit with negative brake system
- 1 dynamometer for direct reading of pulling value with load-limiter device
- Thermally treated steel bull-wheels
- Automatic reel-winder suitable for steel reel 1100÷1400 mm
- Rigid axle with tyres for towing up to 30 km/h
- Balanced top lifting point and anchoring attachments
- Front pulley roller guided device for underground cabling

## OPTIONAL DEVICES

- **069.3** Preset for digital data recorder and counter-meter
- **042** Counter-meter device

\* According to the EC directive 97/68/CE with subsequent amendments and additions.

Performances of the machine without optional devices, at sea level and temperature 20°C.

Dimensions and weights are without optional devices. All data may change without notice. Images and drawings are indicative only.