



P70.B MAX PULL 70 KN

Hydraulic puller 70 kN fit to pull one rope in stringing operations of overhead transmission lines and optics fibre cables.

**MAX PULL**

70 kN

**MAX SPEED**

60 m/min

**MAX ROPE**

16 m/min

**BULL-WHEELS**

2 x Ø 325 mm



FEATURES

BULL-WHEELS	2 x Ø 325 mm
NUMBER OF GROOVES	7
MAX ROPE DIAMETER	16 mm
MAX JOINT DIAMETER	45 mm
DIMENSIONS L x W x H	3590 x 1640 x 1830 mm
WEIGHT (WITHOUT ROPE)	1500 kg

ENGINE

FEEDING	diesel
POWER	36 kW / 36 kW *
COOLING	water
STARTING	12 V

CONFIGURATION

- Multi-grooved steel bull-wheels
- 1 dynamometer for direct reading of pulling value with load-limiter device
- Metallic protection cover on the engine and hydraulic parts
- Electronic instrument by-pass
- Safety negative hydraulic brake
- Oil cooling system
- Reel-winder arms with automatic rope-winder and hydraulic lifting system fit for reel up to max. Ø 1400 mm
- Single rigid axle, adjustable towing bar and manual parking brake fit for towing at low speed on the job-site
- N° 2 mechanical stabilisers on the pulling side
- N° 2 mechanical stabilisers on the reel-winder side
- Anchoring and lifting points

PULL PERFORMANCES

MAX PULL	70 kN
SPEED AT MAX PULL	14 m/min / 14 m/min *
MAX SPEED	60 m/min
PULL AT MAX SPEED	13 kN

OPTIONAL DEVICES

- 007 Chassis with damped axle, overrun brake and drawbar for towing on road (homologation excluded)
- 037.2 Compact remote control by cable. Cable length = 10 m
- 038.1 Radio remote control. Complete with display and 5 m long back-up cable
- 082 Device for pipe refurbishing. Fit for setting the max. pull force which allows to maintain the force set even at speed 0 m/min
- 047 N° 2 hydraulic stabilisers on the pulling-side
- 051.3 Motorised rubber crawler system. Complete with front hydraulic plough and radio-remote control for the crawler system and the machine pulling operations

* According to the EC directive 97/68/CE with subsequent amendments and additions.

Performances of the machine without optional devices, at sea level and temperature 20°C.

Dimensions and weights are without optional devices. All data may change without notice. Images and drawings are indicative only.